

Permaflex Mat 225

Glass fibre mat reinforcement, 225 g/m² — for liquid-applied membranes

Description

Glass fibre mat of 225 g/m² weight, suitable for the reinforcement of liquid-applied membranes.

Fields of application

- Reinforced Permaflex polyurethane systems
- Local reinforcement of liquid waterproofing membranes in difficult areas and details

Properties and advantages

- Enhances the crack-bridging properties of the waterproofing system
- Facilitates the application of increased and uniform thickness for the waterproofing system
- Significantly increases the mechanical strength and durability of waterproofing systems
- Easily and quickly applied
- Adapts to difficult areas and details with complex geometry

Technical characteristics

Mass per unit area	225 g/m²
--------------------	----------

Instructions for use

After the appropriate substrate preparation, apply the first layer of the waterproofing coating according to its own application instructions. While this layer is still fresh, place the Permaflex Mat reinforcement onto the surface and work it into the coating, taking care that no wrinkles or bubbles form. Apply a second layer of coating on top so that the glass fibre mat is fully embedded between the two layers (wet-on-wet application, mat sandwiched between the two coats).
Overlap each section by a minimum of 50 mm.

Product data

Colour	White
Packing	Rolls of 120 m², 95 cm wide. Also supplied by the metre, and in detailing rolls 10 cm and 20 cm wide.
Storage	Unlimited shelf life. Store in original packing, without wrinkles, indoors, in dry conditions between +5°C and +35°C.